



# 400nm, 15mW Fiber-Coupled Laser Diode with Photodiode, SM Fiber, FC/PC Connector

## RLS / 400NM-15MW-PD-SMF

### OPTICAL SPECIFICATIONS

- Output Wavelength: 400 nm  $\pm$ 5 nm
- Output Power: 15 mW
- Spectral Width (FWHM): 2.0 nm
- Wavelength Temp. Coefficient: 0.05 nm/ $^{\circ}$ C
- Beam Type: Gaussian Beam
- Laser Type: Fabry-Perot
- Includes Integrated Photodiode

### FIBER SPECIFICATIONS

- Fiber Type: Single Mode Fiber
- Fiber Core: 3  $\mu$ m
- N.A.: 0.12
- Fiber Length: >80 cm
- Fiber Connector: FC/PC (Other Types Available; Inquire)

### ELECTRICAL SPECIFICATIONS

- Threshold Current: 35 mA (typ)
- Operating Current: 90 mA (typ)
- Operating Voltage: 5.0 V (typ)
- Max LD Reverse Voltage: 2.0 V
- PD Current: 0.3 mA
- PD Reverse Voltage Max: 30 V

### GENERAL SPECIFICATIONS

- Operating Temperature Range: -10 $^{\circ}$ C – 70 $^{\circ}$ C
- Recommended Operating Temp: 25 $^{\circ}$ C
- Storage Temperature Range: -40 $^{\circ}$ C – 85 $^{\circ}$ C
- Lead Soldering Temperature: 260 $^{\circ}$ C, 10 sec.

