



976nm Pre-Configured Fiber-Coupled Laser Diode Source 10W, Multi-Mode Output



980LD-3-4-1 / LASER-DIODE

- o 10 Watt Output Power
- o Spectral Width 3.5 nm
- o Open-Frame Controller, Replaceable Laser
- o 105µm Core Fiber-Coupled, NA 0.15, SMA905 Terminated
- o USB-Connected Operation



LASER
DIODE
SOURCES



CW LASER SOURCE SYSTEM

This 10 Watt, 976nm, CW source system is built around a highly reliable fiber-coupled laser diode. The system is preconfigured and pretested, and is delivered ready-to-run.

The CCM laser source system features open-case construction: the laser, heat-sink, and controller electronics are contained in an open case to provide access to the laser diode as application requirements evolve.. The source system is easily operated using the included GUI over USB interface, and multiple systems can be operated by the same computer.



980LD-3-4-1 / LASER-DIODE / CCM SPECIFICATIONS

| | |
|---------------------------------------|---|
| Laser Output Specifications | Wavelength: 976 nm (\pm 3 nm) Spectral Width: 3.5 nm Output Power: 10 W Optical Fiber: 105 μ m Core Multimode Fiber NA: 0.15 |
| Laser Diode Controller Specifications | Current Range: 0 - 13 Amps Compliance Voltage Range: 0 - 23 Volts Current Stability: \pm 0.05% Laser Diode Set-Point Adjustment Resolution: 0.05 Amps Max. Modulation Rate: 100 kHz |
| TEC Controller | Temperature Control Range (typ): 15 - 40°C Temperature Stability (typ): 10 mK TEC Power: > 150 Watts |
| Modulation Specifications | Pulse Duration: 10 μ s to CW (External Source) Trigger: External Only Externally Adjustable CW Offset in Pulse Mode |
| User Interface and Power Input | USB with GUI Software Includes Control Software Libraries : DLLs, Hexa, Labview VI Required Power Supply : 24 VDC (not included; see below) Recommended Power Supply: EA-PS 2042-20B (from Newark) |
| Dimensions | 238 mm x 119 mm x 112 mm |



Offered by
LASER LAB SOURCE



**LASER
DIODE
SOURCES**

PRODUCT SALES AND SERVICE

Unlimited phone and email support is provided for products purchased through Laser Lab Source. Orders for this product are fulfilled by Laser Lab Source in North America and select international regions. It is manufactured by AeroDIODE, Talence, France.

PRODUCT WARRANTY

This product is sold with a full one-year warranty. It is warranted to be free from defects in material and/or workmanship for a period of one year from the date of shipment.



Laser Lab Source, a division of Research Lab Source, Inc.
670 S. Ferguson St., Suite 3
Bozeman, MT 59718 USA

Phone: 406-219-1472

www.LaserLabSource.com

AeroDIODE

Rue François Mitterrand Institut d'Optique d'Aquitaine
33400 Talence
FRANCE