



*This product is sold
and supported
in the USA by*



LASER LAB SOURCE
marketplace for **Scientists & Engineers**

Laser Diode Part Number: 808LD-5-0-0

contact@laserlabsource.com | 800-887-5065

808 nm laser diode

100 W / 200 μm fiber*

Reference: 808LD-5-0-0

Technology : Multiple emitters Multimode

SPECIFICATIONS	Unit	Min	Typ	Maximum
Optical parameters				
Output Power	W	100		
Center Wavelength	nm	805	808	811
Spectral Width (FWHM)	nm		4.0	7.0
Threshold Current	A		1	1.5
Operating Current	A		9.5	10.0
Operation Voltage	V		27.0	
Conversion Efficiency	%		40	
95% power with NA	NA		0.18	
Wavelength shift w Temperature	nm/°C		0.35	
Slope Efficiency	W/A		13	
Storage Temperature	°C	-30		70
Case Operating Temperature	°C	15	25	55
Fiber Buffer/tube Diameter	μm		320/900	
Fiber Clad Diameter	μm		220*	
Fiber Core Diameter	μm		200*	
Numerical Aperture	NA		0.22	
Fiber length	M		1.5	
Soldering Temperature	°C			260
Soldering time	s			10
Fiber connector	Option (SMA-2 HIGH POWER)			
ROHS Compliant	Yes			

Please solder the pins when the level of current is over 6A

- Possibility for a 105/125μm fiber - contact us as the LIV characteristics above are different

Form factor:

