

## 520nm, 50mW Fiber-Coupled Laser Diode | Single-Mode Fiber, FC/PC Connector

### RLS / 520NM-50MW-SMF

#### OPTICAL SPECIFICATIONS

- Output Wavelength: 520 nm  $\pm$ 10 nm
- Output Power: 50 mW
- Spectral Width (FWHM): 2.0 nm
- Wavelength Temp. Coefficient: 0.05 nm/ $^{\circ}$ C
- Beam Type: Gaussian Beam
- Laser Type: Fabry-Perot

#### FIBER SPECIFICATIONS

- Fiber Type: Single Mode Fiber
- Fiber Core: 3  $\mu$ m
- N.A.: 0.12
- Fiber Length: >80 cm
- Fiber Connector: FC/PC (Other Types Available; Inquire)

#### ELECTRICAL SPECIFICATIONS

- Threshold Current: 70 mA (typ)
- Operating Current: 290 mA (typ)
- Operating Voltage: 7.0 V (typ)
- Max LD Reverse Voltage: 2.0 V

#### GENERAL SPECIFICATIONS

- Operating Temperature Range: -10 $^{\circ}$ C – 60 $^{\circ}$ C
- Recommended Operating Temp: 25 $^{\circ}$ C
- Storage Temperature Range: -40 $^{\circ}$ C – 85 $^{\circ}$ C
- Lead Soldering Temperature: 260 $^{\circ}$ C, 10 sec.

