




1550nm, 80 MHz Fiber-Coupled Acousto-Optic Modulator

1550AOM-1 / FIBER-OPTIC-AOM

*This product is sold
and supported
in the USA by*



LASER LAB SOURCE
marketplace for **Scientists & Engineers**

contact@LaserLabSource.com

800.877.5065

Fiber coupled AOM

Standard version – 1550 nm

Reference: 1550AOM-1

Technology/Crystal : TeO₂*

SPECIFICATIONS	Unit	Min	Typ.	Maximum	Comments
Material			TeO ₂		
Wavelength	nm	1470	1550	1630	Customizable
Average optical power handling	W			0.5	
Peak optical power handling	KW			0.5	
Insertion loss**	dB	2.0	2.5	3.0	
Extinction ratio (1 st order on/off)	dB	50	55		
Rising time	ns			50	
Frequency	MHz		80		
Frequency shift	MHz		+/- 80		
RF Power	W		2.5		
Input Impedance	Ω		50		
Electrical input interface			SMA		
Fiber type		PM1550			Customizable
Fiber length	m		1		Customizable
Pigtail termination		FC/APC			Customizable
Working temperature	°C	-20		60	
Storage temperature	°C	-30		70	
Dimensions (without fiber boots)	mm	60*25*12.5			
Mounting holes diameter	mm		3		

*: See our tutorial : [fiber modulator](#)

** : Insertion loss over the nominal wavelength ±50 nm. Add 0.5 dB to cover the full wavelength range

