


940nm, 100 MHz Fiber-Coupled Acousto-Optic Modulator

940AOM-1 / FIBER-OPTIC-AOM

*This product is sold
and supported
in the USA by*



LASER LAB SOURCE
marketplace for **Scientists & Engineers**

contact@LaserLabSource.com

800.877.5065

Fiber-coupled AOM (Acousto-Optic Modulator)

Standard version – 940 nm

Reference: 940AOM-1

Technology/Crystal : TeO₂*

SPECIFICATIONS	Unit	Min	Typ.	Maximum	Comments
Material			TeO ₂		
Wavelength	nm	900	940	980	Customizable
Max Average optical power	W			5	
Insertion loss	dB	1	1.5	2.0	
Extinction ratio (1 st order on/off)	dB	50			
Return loss (RF ON)	dB	40			
Rising time	ns		45	50	
Frequency	MHz		100		
Frequency shift	MHz		+/- 100		
RF Power	W		1.5	1.8	
Input Impedance	Ω		50		
Electrical input interface			SMA		
Fiber type		PM980			Customizable
Fiber length	m		1		Customizable
Pigtail termination		FC/APC			Customizable
Working temperature	°C	-20		60	
Storage temperature	°C	-30		70	
Dimensions (without fiber boots)	mm	60*25*12.5			
Mounting holes diameter	mm		3		

*: See our tutorial : [fiber modulator](#)

