

## APD4B-29-1.5G-W

### OVERVIEW

APD4B-29-1.5G-W is the InGaAs avalanche photodiode coupled to an optical fiber and packaged into a hermetic case

### MAIN FEATURES

- Bandwidth: 1.5 GHz
- Spectral range: 1000 - 1650 nm
- Typical responsivity: 1.0 A/W at 1310 nm and M = 1
- Package types: coaxial with or without bracket, 14 pins DIL
- Low back reflection, return loss RL > 40 dB
- Low dark current typ. <1 nA

### APPLICATIONS

- Optical fiber communication systems
- OTDR

### ORDERING INFORMATION

## APD4B-29-1.5G-W-X-X-5-X-X-X

#### Optical matching

**R40:** back reflection -40 dB (SM1 and SM3 fiber)

**R25:** back reflection -25 dB (MM5 fiber)

#### Case type

**COAX:** compact coaxial

**COAXB:** compact coaxial with double-sided bracket

**DIL:** 14 pins DIL with thermal stabilization (TEC and thermistor)

#### Fiber type

**SMT:** SM, [Corning Titania-Clad](#), furcation tubing Ø0.9 mm, ultrasmall bending radius 2.5 mm

**SM1:** SM, G.657.A1, [Corning SMF-28 Ultra](#), furcation tubing Ø0.9 mm or **BSM1** Ø0.25mm

**SM3:** SM, G.657.B3, [Corning ClearCurve ZBL](#), furcation tubing Ø0.9 mm or **BSM3** Ø0.25mm

**MM5:** MM, [50/125. OM2](#), furcation tubing Ø0.9 mm

Other type: on request

#### Connector type

**FA:** FC/APC (SM1, SM3, SMT)

**FU:** FC/UPC (SM1, SM3, SMT, MM5, MM6)

**SA:** SC/APC (SM1)

**SU:** SC/UPC (SM1)

**N:** no connector

Other type: on request

#### Fiber length

**0.5:** 500+/-50 mm

**1.0:** 1000+/-100 mm

Other length: on request

# APD4B-29-1.5G-W

## ABSOLUTE MAXIMUM RATINGS


Parameter		Value	Unit	Conditions
Reverse current	$I_R$	2	mA	
Forward current	$I_F$	10	mA	
Operating temperature	$T_{op}$	-40 ÷ +85	°C	Package COAX, COAXB
Operating temperature	$T_{op}$	-40 ÷ +50	°C	Package DIL
Storage temperature	$T_{stg}$	-40 ÷ +85	°C	
Soldering temperature	$T_{sold}$	260	°C	Max. 5 seconds

## ELECTRICAL-OPTICAL CHARACTERISTICS (T = 25 °C)


Parameter		Min	Typ	Max	Unit	Conditions
Operating wavelength		1000		1650	nm	
Responsivity @0.95V <sub>BR</sub>	R40	R	12		A/W	λ = 1310 nm, SM1, SM3, V <sub>R</sub> = 0.95V <sub>BR</sub>
	R25		8			
Return loss	R40	RL	35	40	dB	SM1, SM3 MM5
	R25		20	25		
Breakdown voltage	V <sub>BR</sub>	40	55	70		I <sub>d</sub> = 100 μA
Breakdown voltage temperature coefficient ΔV <sub>BR</sub> /ΔT	δ		0.09		V/°C	T = 25 °C
Dark current	I <sub>d</sub>		0.3	1	nA	V <sub>R</sub> = 0.9 V <sub>BR</sub>
Total capacitance	C <sub>t</sub>		0.4	0.6	pF	f = 1 MHz
Bandwidth	BW	1.5			GHz	M = 10

## APD4B-29-1.5G-W

## CHARACTERISTICS (T = 25 °C)




## APD4B-29-1.5G-W




### COAX




BACK VIEW



PINOUT  
#5




Download more information




### COAXB



BACK VIEW




PINOUT  
#5





Download more information



# APD4B-29-1.5G-W



Download more information



# APD4B-29-1.5G-W

---

Characteristics, data, materials and structures specified in this datasheet are subject to change without notice. Please refer to the latest specification before use of the products.

## Safety and handling cautions

1. Avoid smashing and burning of the module. Avoid storing and using the module in conditions where water, organic solvents or aggressive acids or bases may contact the module or where there is a possibility of exposure to corrosive gases, explosive gases, dust, salinity or other harsh conditions. The module should be disposed as special industrial waste.
2. Exceeding absolute maximal ratings even for a short time can cause permanent damage of the module.
3. The module is sensitive to and can be broken by ESD (static electricity).

## Conflict Minerals Policy Statement

LasersCom LLC achieves business objectives and customer needs with social responsibility. We do not support or contribute to the violence and human rights violations associated with the mining of conflict minerals coming from Conflict Regions according to US "Dodd-Frank Act". When possible, our suppliers' conflict mineral statements are reviewed. We do not directly purchase Conflict Minerals from any source and do not knowingly procure any parts and products containing Conflict Minerals from Conflict Regions.

## RoHS Compliance Statement

Restriction of Hazardous Substances (RoHS) directive (Directive 2011/65/EC amended with Directive (EU) 2015/863) is the directive aimed at reducing the harmful environmental impact of waste electrical equipment by restricting the use of known dangerous substances. Based on information received from our supply sources, LasersCom LLC hereby states that the banned substances listed in the RoHS directive are not found in the parts and materials used above the threshold level listed other than exceptions approved by the European Commission.

## REACH Compliance Statement

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) is a European Union regulation 1907/2006/EC that addresses the production and use of chemical substances, and their potential impacts on human health and the environment. Based on information received from our supply sources, LasersCom LLC hereby states compliance of the parts and materials used in manufacturing to REACH regulation. LasersCom LLC does not manufacture or import any substances or preparations as defined under REACH.